



# VENTED SILL PLATE

## RAISES THE WOOD STRUCTURE OF POTENTIALLY WET SURFACES.

Teksill VSP lifts the wood structure and allows air and water to circulate freely under the structure. Teksill VSP is available in 48-inch length and attaches directly to the wood piece (2 X 4 or 1 X 4) with one CLICK.

The vented sill plate contains 10% recycled plastic and is recyclable. It can be used for LEED projects.

Teksill VSP is impervious to water and most chemicals. It is not affected by temperature changes. Teksill VSP will not rot and will not support mold growth.



## APPLICATIONS

- Under basement partition walls to protect the wood structure from moisture.
- Under partition walls mounted on a radiant slab to allow the heat to dissipate better.
- Under building partition walls to reduce damage caused by water disaster.
- Under a subfloor to protect the wood structure from moisture.

## BENEFITS

- Attaches directly to the piece of wood without tools.
- Protects the wood structure from moisture.
- Allows air to circulate under the structure of walls and floors.
- In case of water disaster, the water can run under the wall thus limiting the damage.
- Following a major water disaster, the wood structure can be cleaned, decontaminated and dried easily.
- Improves indoor air quality.
- Not affected by water and humidity.
- Will not support mold growth.
- 25 year limited warranty



## SPECIFICATIONS

- Standard size is 3-5/8" X 48"
- Lift the structure by 11/16"
- Can be used on a wide range of loadings (1-50psi)\*  
\* non-load-bearing walls

Quantity of pieces per box      20 pieces (80 linear feet)

The merchant can sell individually

For more information:

✉ info@teksill.com    🌐 www.teksill.com

